



Product specification sheet

Floor/ground socket IP 67 – for double / hollow floors

Designation:

Type: STAKOHOME-7501-A 1x socket 230V
Type: STAKOHOME-7501-Anw 1x RJ45 Cat.6a
Other types (different instrumentation) upon request

Specification:

The unit is made of solid PVC. The screwing lid and frame from solid aluminium with appearance of high grade steel, anodized. The screwing lid can be open only using a special key. Providing this design is correctly installed, passenger vehicles can drive over it. The assembly unit/box is suitable for outdoor use, IP 67. Side inlets 2x M25.

<u>Assembly instructions:</u> Use cable screwing with ingress protection IP67. Press the ground socket with spirit level into the mortar bed etc., level with the terrain according to the screed or similar material. The rest shall be later filled up with mortar. The floor box can also be used for installation in double floors (the glue is applied under the upper frame, i.e. between the frame and the floor covering).

The box must be regularly cleaned, otherwise the ingress protection level cannot be guaranteed. Only authorized electrician specialist can install the connection.

Maintenance: the socket must be checked regularly and free of dirt inside. The socket cover must be tightened firmly / well with a wrench to ensure that the socket is covered.





Scope of application: Outdoor and indoor areas, water-proof if closed, ingress protection IP67. **Accessories:** Type: STAKOHOME-7703-2 Extension for protection against dust (Ø80 x 70mm)

The extension is made of gray solid PVC. Due to the small hole for the cable, it is no longer an IP67 protection. Accessories must be purchased (if necessary)

Technical data:

Material: Unit from special PVC-U, aluminium lid and frame, high grade steel appearance, anodized

PVC-U: Special characteristics: No elasticator, good mechanical solidity, resistance to acids and alkali. Terraces, garages, house vicinity, car saloons, exhibition areas, commercial areas, swimming

pools, etc.

Dimensions: upper visible frame Ø 114mm, box Ø 90mm x 82mm (height)

Weight: approx 600 g Load-carrying capacity: 900kg

Sockets/instrumentation: 230V, RJ45, XLR, USB

Note: Printing errors and alterations reserved

Showroom a doručovací adresa: Aloisovská 934/8, 198 00 Praha 9, Hloubětín







Technical sheet

Floor box IP67


Designation:


Accessories:

Type: STAKOHOME-7501-A 1x socket 230V
Type: STAKOHOME-7501-Anw 1x RJ45 Cat.6a
Other types (different instrumentation) upon request

Type: STAKOHOME-7703


Note.: Side inlets 2x M25






Extension for protection against water and dust (Ø80 x 70mm)

Note: when installing in paving or wood, etc., it is necessary to mill two 5 mm grooves in the floor (in the picture).





Note: Printing errors and alterations reserved

Showroom a doručovací adresa: Aloisovská 934/8, 198 00 Praha 9, Hloubětín



Stakohome Network s.r.o.

IČ: 27213064, DIČ: CZ27213064

tel.: +420 226 517 522

fax: +420 226 517 379

stakohome@stakohome.cz

www.stakohome.cz

www.inteligentni-byt.cz

Fakturační adresa: Podnikatelská 565, 190 11 Praha 9, Běchovice





If an extension is used, the cover is unscrewed and the appropriate extension is screwed in instead of the cover. The required device is connected and the lid is screwed back onto the attachment.

The black rubber cover is pulled onto the attachment. The connected cables (from appliances / equipment) pass through the holes in the PVC extension and under the black protective cover downwards.

The attachment is made of gray solid PVC, suitable as protection against dust and dirt, for example. Due to the small hole (in the upper part of the extension) for the cable, it is no longer an IP67 protection.

The STAKOHOME-7703-2 attachment can be used for the STAKOHOME-7501-A floor box.





pic.: extention STAKOHOME-7703-2 with floor box STAKOHOME-7501-A

